

1 STRUCTURAL 53/4 NONSTRUCTURAL 5 STOCKING 16, 18 AND 20 LENGTH

Ply-Trim[®] Stair Stringer Components

► 100% USABLE MATERIAL

- ► COST EFFECTIVE SOLUTIONS STRAIGHT TRUCKS OF 16' LENGTHS, NO RANDOM TALLIES (BETTER INVENTORY CONTROL)
 - ► CNC MACHINE READY
 - ► UNIFORM THICKNESS



Technical Specifications

THICKNESS: 3/4" NONSTRUCTURAL AND 1" STRUCTURAL

STANDARD FINISH: PRIME COATED – 4 SIDES
STANDARD DEPTH: 9-1/4" AND 11-1/4"

Standard Lengths: 16', 18' and 20'

SPECIAL ORDERS: UPON REQUEST - CALL FOR QUOTE

Engineering Specifications-ASTM-D195

Static Bending – Edge (Beam) – F_b = 4,100 PSI Compression Short Member = 2,500 PSI Compression Long Member = 3,000 PSI

Structural Stair Stringer Physical & Packaging Specifications				
Size	WEIGHT/ LIN. FT.	APPROX. WEIGHT PER UNIT/16' LENGTH	PIECES PER UNIT	APPROX. LIN. FT. PER TRUCK LOAD
3/4" x 9-1/4" (7 PLY)	1.45 lbs	2320 lbs	105	26,880
3/4" x 11-1/4" (7 PLY)	1.97 lbs	2648 lbs	84	21,504
1" x 9-1/4" (10 PLY)	2.28 lbs	2736 lbs	75	19,200
1" x 11-1/4" (10 PLY)	2.78 lbs	2669 lbs	60	15,360



PLY-TRIM WEST, INC. 2920 S. Cushman Drive

2920 S. Cushman Drive Tacoma, WA 98409 1-800-545-4454 253-572-7300 Fax 253-272-5270 www.ply-trimwest.com